



## 2023 CLASS REPRESENTATIVES

# 13,000 Farm Stock

### General Rules:

- 1) Weight 13,000#
- 2) Speed Limit 8mph
- 3) 3000rpm limit
- 4) Non cut 18.4 x 42 or 20.8 x 38 maximum tire size
- 5) Gear shifting using clutch while pulling not allowed
- 6) Tractor and driver must scale or results in DQ
- 7) No rear dual wheels allow
- 8) 2 hook grace pull allowed to allow for rules to be followed by tractor
- 9) Wide front end required
- 10) Must have working PTO
- 11) If pulling in or a member of Outlaw Farm not allowed to pull in 13000 Farm

### Safety Rules:

- 1) RPM plug in sensor for RPM sled box FVP P/N: 3316 Required for members, non-member requirement at discretion of Club Tech Official.
- 2) Cross bolts in exhaust pipe (Grade 8) Recommended
- 3) Wheelie bars required for members, at officials discretion for non-members
- 4) Fenders and/or floorboards supporting weight of driver required
- 5) Kill switch mounted at rear of vehicle required
- 6) Must have positive stop on injection pump for high idle

### Engine:

- 1) OEM Motor and Block. Block is not to be altered in any way externally for mounting of fuel injection pumps and remain in stock location. Internal webbing and water jacket to remain intact with provisions to re-bore block. OEM Transmission must be stock appearing. No aftermarket gear boxes. Clutch housing, transmission case, rear end

housing must be OEM or equivalent. No tube frames Must meet Tech and Class rep approval

2) Must have OEM cylinder head, intake manifold and exhaust manifold No filler heads, single feed intake manifolds only. No headers or custom intakes manifolds.

3) No turbo limit

4) RPM plug in sensor for RPM sled box FVP P/N: 3316 Required for members, non-member requirement at discretion of Club Tech Official

5) No water injection allowed

6) Stock appearing injection pump matching OEM for engine

7) Full Sheet metal to be in stock location and appearance. Including Hood and grill.

8) No intercoolers or cooling devices allowed

**Hitch:**

1) 20" max drawbar height

2) Haslag hitches not allow