



## **2022 CLASS REPRESENTATIVES**

**LUCAS ELROD**

**DAVE CLARK – (608) 632-0964**

# 8,500 TOO HOT TO FARM RULES

**\*\*All Rules Are Locked In For 3 Years, Unless 100% Vote Overturns**

### **Fireproof Jacket, Pants and Helmet are Required to be worn while hooked to sled.**

Must have Weld on Hubs for Pressed Steel. **No** Cast Centers.

**3,000 RPM Max.** Tractors will be checked at each pull. Must have RPM sensor with plug in at rear of Tractor to hook to the sled.

Speed Limit of **17 MPH \*\*NEW FOR 2019**

Weight Limit of **8,500 lbs. \*\*NEW FOR 2019**

### **Required Equipment**

OEM Ag rear end.

Drawbar must be a minimum of 18" from center of rear axle.

Drawbar Maximum Height of 20" Stationary in all directions.

Maximum Wheelbase of 114"

Maximum Frame length from center of rear axle 156"  
working Breaks

Must have Fenders.

Maximum Tire size of 18.4-38 TOP CUT ONLY(NO CUT ON FACE OF LUG) **\*\*NEW FOR 2019**

Clutch Blanket if tractor has a Cast Iron Flywheel.

Stabilizer bars. Pads to be no higher than 10" from the ground. Pads must extend beyond the radius of the tire.

Air Kill switch. Must be spring loaded. With activating cable mounted at the rear of the tractor in clear sight to hook to the sled.

Dead man Throttle (must return to idle when released)

Turbo must be under Hood

Side Shields

Wide Front End

Cross Bolts mounted in exhaust pipe, 2 3/8" grade 8 bolts.

Tie bars mounted to the rear axle and extending forward of the flywheel and mounted to the frame.

Fuel dump valve able to be controlled from seat. (Recommended)

Roll Bar or Roll Cage

Seatbelt

Front Ski Bars, in line with the frame rails. Pads to be below front wheel hubs. (Recommended)

540 Cubic Inch limit

Stock OEM Manifolds

May run a stock intercooler. NO Icebox.

May Use Water Injection, Water only.

Diesel Fuel Only

Drivers must be at least 14 years of age with driving certificate and parental consent to compete in the class.

**All General Rules Apply.**