

6000 LB Super Stock 2WD

Southwest WI Pullers 2026 Rules

General rules

- 6000 lb max weight
- 35" max dot approved tire, no cuts, sipe, or barred tires
- Fuels allowed, gas, race gas, E-85. Not allowed, Methanol, Nitrous, Diesel
- Naturally aspirated engines only. No power adders, turbos, nitrous, blowers
- Factory EFI allowed, no Hilborn style or similar allowed
- Must have firewall
- Front hanging weights/ weight box allowed. If wheelbase exceeds 133" no front hanging weights or weight box allowed
- Must have brakes, driveline brakes allowed
- Headers allowed, must point upwards or downwards

Safety rules

- Vehicle must have a 2.5# fire extinguisher mounted within reach of the driver
- Seat with back required and minimum lap belt required
- Fire jacket required in all vehicles, minimum of SFI 3.2B. fire resistant gloves, fire resistant head sock, fire resistant pants, fire resistant shoes meeting SFI spec 3.3 highly recommended
- Helmets required must meet Snell 2010 minimum, or SFI spec 31.1, 31.2, 41.1, 41.2
- Recommended Neck Collars
- Pants and closed toe shoes required
- Must have bumper or sled stops
- Must have SFI harmonic balancer

- Steel flywheel and bellhousing required
- Automatic trans must have blankets
- Scatter shield or blanket around clutch and flywheel recommended except automatics
- No fuel tanks or fuel components in cab
- No more than 12" of rubber fuel line in engine bay allowed, Steel braided or steel line required
- 2 driveshaft safety loops and knuckle guards (1/4" steel or 3/8" aluminum) required
- Kill switch mounted at rear of vehicle required, must kill ignition and electric fuel pump if equipped
- Side shields required in engine bay, must be length of engine, rigid mounted, and extend from top of frame to above sparkplug
- Front and rear windows required, glass or plexiglass
- Reverse light required
- If there is no bed floor, you must have bed liner or tonneau cover
- No batteries in the cab

Drivetrain

- Engine must be in factory location, motor plates allowed
- Aftermarket cast or aluminum heads with OEM valve location and configuration allowed
- Any single carburetor or OEM EFI allowed
- No tunnel rams
- 11" max intake height from China wall to carburetor base
- No dry sump oil systems
- Tube or custom frames are not allowed
- One planetary allowed, either in OEM married transfer case form, or in OEM style 2 speed rear end
- No profab style drop box, reversers, or aftermarket 3 speeds. OEM transmissions, transfer cases only

- Traction bars and blocked or solid rear suspension allowed
- No dual rear wheel allowed
- No altered wheelbase, tires must fit in OEM location wheel wells

Hitch

- Hitch height up to 30”
- Hitch must be rigid in all directions
- Drawbar length to be minimum of 27% of truck wheelbase from center of rear axle to point of hook
- Hitch mounting point no further forward than center of rear axle
- Hitch hook loop must have 3.75” inner diameter