



**2024 CLASS REPRESENTATIVES**  
**LOGAN SCHMERBACH**  
**KEVIN JASPER**

**outlaw farm**

**General Rules:**

- 1) Weight 12,000#
- 2) Speed Limit 12mph
- 3) 3000rpm limit
- 4) Non cut (front or top of lug) 18.4 x 42 or 20.8 x 38 maximum tire size
- 5) Tractor and driver must scale or results in DQ
- 6) No rear dual wheels allow
- 7) Wide front end required
- 8) If pulling in or a member of Outlaw Farm not allowed to pull in 13000 Farm

**Safety Rules:**

- 1) RPM plug in sensor for RPM sled box FVP P/N: 3316 Required for members, non-member requirement at discretion of Club Tech Official.
- 2) Cross bolts in exhaust follow General Rules (Safety Rule #7)
- 3) Wheelie bars required for members, at officials discretion for non-members
- 4) Fenders and/or floorboards supporting weight of driver required
- 5) Kill switch mounted at rear of vehicle required
- 6) Must have positive stop on injection pump for high idle
- 7) T-bar or ROPS extending above driver with lap belt required

**Engine:**

- 1) OEM Motor and Block. Block is not to be altered in any way externally for mounting of fuel injection pumps and remain in stock location. Internal webbing and water jacket to remain intact with provisions to re-bore block. OEM Transmission must be stock appearing. No aftermarket gear boxes. Clutch housing, transmission case, rear end housing must be OEM or equivalent. No tube frames Must meet Tech and Class rep approval

- 2) Must have OEM cylinder head, intake manifold and exhaust manifold No filler heads, single feed intake manifolds only. No headers or custom intakes manifolds.
- 3) Maximum of S300SX-E 2.42" 61.44mm P/N 13009097053 out of the box turbo
- 4) RPM plug in sensor for RPM sled box FVP P/N: 3316 Required for members, non-member requirement at discretion of Club Tech Official
- 5) No water injection allowed
- 6) Stock appearing injection pump matching OEM for engine
- 7) Full Sheet metal to be in stock location and appearance. Including Hood and grill.
- 8) No intercoolers or cooling devices allowed

**Hitch:**

- 1) 20" max drawbar height
- 2) Haslag or manufactured hitch allowed, top link hitch of any kind not allowed
- 3) 18" minimum from center of rear axle to end of drawbar