



2023 CLASS REPRESENTATIVES

MATT BIRD (608) 604 -4104

JOHN HARRIS (608) 604 -9964

6500 OUTLAW

Class Allows both Trucks & Tractors

General Rules:

- 1) No Speed Limit - NEW 2023
- 2) Tractor - 18.4x38 maximum tire size
- 3) Trucks - 2wd and 4wd, 35" maximum DOT approved tire
- 4) Single Fuel only allowed: Alcohol, Diesel, Gasoline and Propane.
- 5) No Component style rear end tractors allowed
- 6) No Truck with Drop Box allowed
- 7) Weight 6500#

Safety Rules:

- 1) Vehicle must have a 2.5 # fire extinguisher mounted within reach of the driver
 - 2) Tractor - Roll Cage and approved seat with safety harness required
 - 3) Truck - Seat with back and lap seat belt required
 - 4) Fire suits required in all vehicles, minimum of SFI 3.2. In flip top bodied vehicles without a firewall or working doors, the driver will be required to wear an SFI 3.2A-5 approved suit. B) Fireproof gloves, fireproof head-sock, and fireproof shoes must meet SFI Spec. 3.3. C) All helmets must meet Snell 2010 minimum, or SFI Spec. 31.1, 31.2, 41.1, or 41.2.d) Neck collars are recommended.
 - 5) Tractors - wide front end with ski bars required
- 5a) Front axle support to be made of 2.00" X .095 tubing or 2.00" X .120 mild steel tubing or same material as tractor frame rails. Front axle supports should connect to each frame rail in-line and extend towards front of tractor. Front skid/ front axle support should have radius to prevent digging into track. Front axle support frame should be strong enough to support front end weight of tractor. Support should have a maximum of 4" ground clearance

- 6) Side shields required
- 7) Must have shield around harmonic balancer
- 8) Steel Flywheel Required
- 9) Scatter shield or blanket around clutch and flywheel required
- 10) Tractor - Tie bars extending from rear axle housing to main frame required
- 11) Tractors - Wheelie bars with sled bump stops extending behind rear tires required
- 12) Deadman Throttle with return spring and positive throttle stop required
- 13) Fenders and/or floorboards supporting weight of driver required
- 14) Kill switch mounted at rear of vehicle required

Engine:

- 1) Tractor 370cid and under allowed intercooler Above 370cid not allowed intercooler
- 2) Turbocharger allowed
- 3) Supercharger's not allowed
- 4) Exhaust must exit vertical with cross bolts in pipe for vehicle with turbocharger

Hitch:

- 1) Tractors - 20" max drawbar height and 18" minimum length from the center of axle
- 2) Trucks - maximum drawbar height of 26"