



2022 CLASS REPRESENTATIVES

MITCHELL KLINKNER

13,000 FARM STOCK

13,000 lbs

OEM Motor and Block. Block is not to be altered in any way externally for mounting of fuel injection pumps and remain in stock location. Internal webbing and water jacket to remain intact with provisions to re-bore block. OEM Transmission must be stock appearing. No aftermarket gear boxes. Clutch housing, transmission case, rear end housing must be OEM or equivalent. No tube frames Must meet Tech and Class rep approval.

Must have OEM cylinder head, intake manifold and exhaust manifold for that model or series tractor. No filler heads, single feed intake manifolds only. No headers or custom intakes manifolds.

No turbo limit

3000 RPM limit

RPM plug in sensor for RPM sled box FVP P/N: 3316 Recommended

No shifting after 100 ft

Must have positive stop on injection pump for high idle

Speed limit 8 MPH

Cross bolts in exhaust pipe (Grade 8) Recommended

No water injection allowed

Wheelie bars Recommended

Air shutoff on intake of turbo

Stock appearing injection pump matching OEM for engine

Non cut 20.8x38 or 18.4x42

20 inch hitch height

Full Sheet metal to be in stock location and appearance. Including Hood and grill.

Must have a wide front end. Will be subject to inspection and Southwest Pullers approval.

No intercoolers or cooling devices allowed

\$250 protest rule. If tractor found to be in violation, owner provides SWATP \$250.

Spot RPM checks allowed at anytime

2 hook grace pull allowed to allow for rules to be followed by tractor

Tractor and Driver Must Scale or results in DQ

No Dual Rear Wheels

Must have working PTO

