



2026 CLASS REPRESENTATIVES
JAKE HAMILTON

outlaw gas

General Rules:

- 1) 6300# Maximum weight
- 2) 35" maximum DOT approved tire, Siped tires not allowed
- 3) Single fuel only, pump gas, race gas, E-85. (No alcohol, methanol, ect.)
- 4) Naturally aspirated engines only (no power adders, turbos, nitrous, pro chargers)
- 5) No EFI fuel systems unless factory equipped
- 6) Truck must have firewall, box floor intact, completely gutted interiors not allowed
- 7) Front weight box/hanging weight allowed. Furthest most point not to exceed 60 inches from centerline of front axle. Must be removable by pins or bolts. Wheelbases over 133" not allowed to have front weights.
- 8) Working Brakes on front wheels required, no driveline brakes allowed
- 9) Down swept headers or manifolds minimum required

Safety Rules:

- 1) Vehicle must have a 2.5 # fire extinguisher mounted within reach of the driver
- 3) Seat with back and lap seat belt required
- 4) Fire Jacket required in all vehicles, minimum of SFI 3.2 B) Fireproof gloves, fireproof head-sock Fireproof pants, fireproof shoes meeting SFI Spec. 3.3. Highly Recommended
- C) Helmets Required, must meet Snell 2010 minimum, or SFI Spec. 31.1, 31.2, 41.1, 41.2.
- D) Neck collars are recommended. E) Pants and closed toe shoes required
- 5) Truck Must have Bumper or Sled Stops
- 7) Must have a SFI harmonic balancer
- 8) Steel Flywheel and Bell Housing Required, Must have Blanket on Automatics
- 9) Scatter shield or blanket around clutch and flywheel recommended except automatics
- 10) Must have OEM fuel tank or Fuel Cell in box of truck behind the cab
- 11) No more than 12" of Rubber Hose then Steel Braided or Steel fuel line in engine bay required
- 12) 2 Drive shaft loops and knuckle gaurds (1/4" steel or 3/8" Aluminum) required

13) Kill switch mounted at rear of vehicle required must kill fuel pump if electric

Engine & Driveline:

- 1) Engine must match truck make and be mounted in factory location (motor plates allowed)
- 2) Aftermarket cast or aluminum heads with OEM Valve location & configuration allowed
- 3) Any single carb or efi fuel source allowed
- 4) No tunnel ram or sheet metal fabricated allowed intakes allowed.
- 5) Electric fans, water pumps, vaccum pumps allowed
- 6) Dry sump oilings not allowed
- 7) Tube or custom frames not allowed
- 8) Flatbed allowed but must be useable and cover drivetrain and wheels
- 9) 1-ton drivetrain or smaller required, 8 bolt wheels maximum
- 10) OEM transmissions and transfer cases required
- 11) Aftermarket transmissions, drop box reverser not allowed
- 12) Traction bars and blocked or solid rear suspension allowed
- 13) No dual rear wheels allowed

Hitch:

- 1) 26" hitch height. Reese style adjustable hitches allowed. Draw bar anchor points cannot be further than the center of the rear axle and much be below bed floor
- 2) Hook point must have an opening of 3 3/4 inches