



2026 CLASS REPRESENTATIVES

DAVE CLARK

LUCAS ELROD

8,500 too hot to farm

**All Rules Are Locked In For 2 Years, Unless 100% Vote Overturns

General Rules:

- 2026 1) Weight 8,500#
- 2026 2) Speed Limit 17mph
- 2026 3) 3000rpm limit
- 2026 4) top cut 18.4 x 38 maximum tire size (no cut on face of lug)
- 2026 5) Gear shifting using clutch while pulling not allowed
- 2026 6) Tractor and driver must scale or results in DQ
- 2026 7) No rear dual wheels allow
- 2026 8) No Turbo Limit
- 2026 9) Wide Front End Required

Safety Rules:

- 2026 1) RPM plug in sensor for RPM sled box FVP P/N: 3316 Required for members, non-member requirement at discretion of Club Tech Official.
- 2026 2) Cross bolts in exhaust following general rules (4 3/8" Grade 5 or 2 1/2" Grade 5 Bolts)
- 2026 3) Wheelie bars extending past rear tire required - Must be a maximum of 10" from ground
- 2026 4) Fenders and/or floorboards supporting weight of driver required
- 2026 5) Kill switch mounted at rear of vehicle required
- 2026 6) Must have positive stop on injection pump for high idle
- 2026 7) Dead man throttle required
- 2026 8) Clutch blanket required if tractor has cast flywheel
- 9) Front Ski Bars Recommended, Front axle support to be made of 2.00" X .095 tubing or 2.00" X .120 mild steel tubing or same material as tractor frame rails. Front axle supports should connect to each frame rail in-line and extend towards front of tractor. Front skid/front axle support should have radius to prevent digging into track. Front axle support frame should be strong enough to support front end weight of tractor. Support should have a maximum of 4" ground clearance
- 2026 10) Tie bars mounted to rear axle and extending forward of the flywheel mounted to frame

2026 11) Fuel Shutoff controlled from seat of tractor required

Engine:

- 2026 1) Side shields required
- 2026 2) 540 cubic inch limit
- 2026 3) Stock OEM manifolds
- 2026 4) Stock OEM intercooler allow, no icebox or added intercooler
- 2026 5) Water injection allowed, water only
- 2026 6) Diesel Fuel only
- 2026 7) Turbo must be under hood and exhaust exit upward

Hitch:

- 2026 1) 20" max drawbar height
- 2026 2) 18" minimum from center of rear axle to end of drawbar

Chassis:

- 2026 1) Roll Cage with harness or OEM ROPS with lap belt required
- 2026 2) Must have weld on hubs for pressed steel, no cast centers, Cap bros hubs allowed
- 2026 3) OEM ag rear end
- 2026 4) Working brakes required