



2022 CLASS REPRESENTATIVES

JEFF HELT

3.0 DIESEL TRUCK

All Southwest Pullers are required to wear full fireproof Jacket, Pants and Helmet

THE CLASS RULES FOLLOW THE
PPL 3.0 DIESEL TRUCK CLASS.

No injectables allowed on pulling
chassis trucks

Recommended Rules:

Axle shields are required. Shield to be .060" thickness steel or aluminum. Shield not to be mounted to axle ends or hub bolts. A hole may be cut in one to allow locking in of hubs.

No cast iron clutches or flywheels permitted, must be SFI approved. Trucks with automatic transmissions, refer to General Rules.

SFI bellhousing blankets and/or SFI blow proof bellhousing required

All U-joints must be shielded 360 degrees with 3/8" thick aluminum w/1/8" steel liner or 5/16" thick steel. Shield will be 6 inches long minimum and centered on u-joint. Inside diameter of shield will be no more than 2 inches larger than u-joint.

All intermediate shafts between the transmission and transfer case will be totally enclosed in 3/8" aluminum or 5/16" steel, 1/4" of shaft may be visible.

Fire extinguisher (2.5#) or fire suppression system, Helmets-Snell 90 or better, SFI fire suits, head sock, gloves, shoes, and seatbelts required.

All General Rules Apply