



2026 CLASS REPRESENTATIVES

DAVE CLARK

8,000 Farm Stock

****All Rules Are Locked In For 2 Years, Unless 100% Vote Overturns**

General Rules:

- 2026 1) Weight 8,000#
- 2026 2) Speed Limit 7mph
- 2026 3) 3000rpm limit
- 2026 4) Tractor and driver must scale or results in DQ
- 2026 5) No rear dual wheels allow

Safety Rules:

- 2026 1) RPM plug in sensor for RPM sled box FVP P/N: 3316 Required for members, non-member requirement at discretion of Club Tech Official.
- 2026 2) Cross bolts in exhaust pipe (Grade 5) Recommended
- 2026 3) Wheelie bars recommended for members, at officials discretion for non-members
- 2026 4) Fenders and/or floorboards supporting weight of driver required
- 2026 5) Kill switch mounted at rear of vehicle recommended
- 2026 6) Must have positive stop on injection pump for high idle

Engine:

- 2026 1) OEM Motor and Block. Block is not to be altered in any way externally for mounting of fuel injection pumps and remain in stock location. Internal webbing and water jacket to remain intact with provisions to re-bore block. OEM Transmission must be stock appearing. No aftermarket gear boxes. Clutch housing, transmission case, rear end housing must be OEM or equivalent. No tube frames Must meet Tech and Class rep approval
- 2026 2) Must have OEM cylinder head, intake manifold and exhaust manifold No filler heads, single feed intake manifolds only. No headers or custom intakes manifolds.
- 3) HX35 54mm or equivalent 2" smooth bore inlet turbo limit (no custom slugs or inlets) for 2026 up to 414cid with inline injection pump, no turbo limit for up to 414cid with a rotary pump

- 2026 4) Turbocharger not allowed on engines over 414cid
- 2026 5) No CID limit for natural aspirated tractors
- 2026 6) RPM plug in sensor for RPM sled box FVP P/N: 3316 Required for members, non-member requirement at discretion of Club Tech Official
- 2026 7) No water injection allowed
- 2026 8) Stock appearing injection pump matching OEM for engine
- 2026 9) Full Sheet metal to be in stock location and appearance. Including Hood and grill.
- 2026 10) No intercoolers or cooling devices allowed

Hitch:

- 2026 1) 20" max drawbar height
- 2026 2) Hitch must mount from factory mounting areas

Chassis:

- 1) Maximum wheelbase is 114" and maximum length is 13' from the center of the rear axle 2026 to forward most part of the tractor.

Tires: 1) Allow hard surface spun, groomed, shortened, or top cut 18.4 x 38 tire.

- 2026 Any cutting, grinding, planning, marks or swirls in the tires casing or front, rear, sides of the lug not allowed. Bar Cut, $\frac{3}{4}$ " Full Cut, Full Cut, Full Cut with Point, Extended Cut, Double Cut not allowed.